DATA TRACK SYSTEM
Series 760 - 2 Circuit

CLARTÉ LIGHTING

ADDITIONAL ACCESSORIES



Mid Feed
760-553-1-5203



Current Limiter - Live End Feed
760-198-00-1101-0



Current Limiter - Live Center Feed
760-198-00-1108-0



End Cap
760-555-0-1217



Flexible Connector
760-553-1-1211



California Title 24 Compliant Current Limiter - Live End Feed
760-198-20-2021



California Title 24 Compliant Current Limiter - Live Center Feed
760-198-20-2023

TRACK ADAPTERS

Multi Adapter
760-99-779

Housing: self-extinguishing polycarbonate according to class V0.

Multi Adapter
760-99-698-0

With SELV - safety chip and gold plated spring contact pins.

ORDERING INFORMATION

Ordering Example:

Series — Color
760 – GET204 – WHT
Accessory Type

Catalog Number	Product Description	Circuit Type
Track System		
760-233-10	4' Track	Double Circuit
760-233-20	8' Track	Double Circuit
760-233-30	12' Track	Double Circuit
760-553-2-1201	Live End Feed	Double Circuit
760-555-0-1217	Conduit End Feed	Double Circuit
760-555-2-1206	Linear Coupler	Double Circuit
760-553-1-1208	Live Middle Feed	Double Circuit
760-553-1-1209	Feedable L-Connector	Double Circuit
760-553-1-1212	Feedable T-Connector	Double Circuit
760-553-1-1216	Feedable X-Connector	Double Circuit
760-553-1-5203	Mid Feed	Double Circuit
760-553-1-1211	Flexible Connector	Double Circuit
760-198-00-1101-0	Current Limiter - End	Double Circuit
760-198-00-1108-0	Current Limiter - Center	Double Circuit
760-198-20-2021	Current Limiter - End CA 24	Double Circuit
760-198-20-2023	Current Limiter - Center CA 24	Double Circuit
760-555-0-1217	End Cap	Double Circuit
760-99-779	Multi Adapter	Double Circuit
760-99-698-0	Multi Adapter w SELV	Double Circuit

Color Option (Must Select):

WHT	White
BLK	Black
NA	Natural Aluminum (Only for Track)

ENGINEERING SPECIFICATIONS

Size

- Track available in standard 4', 8' & 12' lengths and measures only 1.375" x .8125" deep.
- Track is capable of being cut to any desired length with a proper saw.

Connectors

- Save time and effort. Simply push connectors into ends of track and eliminate the need for splicing. L, T & X connectors allow the flexibility to build complex patterns.

Specifications

- Track is built from extruded aluminum channel with a .070" wall thickness. Conductors are solid copper buss bar, equivalent to #12 AWG wire. Electrical capacity is 20 amps. End caps and connectors are polarized and are enclosed in injection molded Lexan.

Grounding

- Safety of operation is accomplished automatically by a milled grounding bar. The finger in each connector maintains continuity through the track and building ground system.

Specification sheet subject to change without notice

CLARTÉ *LIGHTING, INC.*
975 N. Todd Ave, Azusa, CA 91702
Tel No. (626) 261-4242 Fax No. (626) 598-3750

Project Name:		Type:	
Catalog Number:		Date:	