


Project Name:		Type:	
Catalog Number:		Date:	


Standard 7.6"OD




Extended Lip Option 9.25"OD



Standard



Extended Lip Option



Key Features

- 6" ID - 7.6" OD
- Fixed
- NON-IC Fixture
- Remote Transformer Optoin
- .02" Uber Thin Trim Lip
- Over 10,000+ fixture custom color finish options
- 100,000+ L70 life

LED Source Details

CREE XML2 LED maximum rating 3,000 mA

- Fixture operating milliamps = 700 mA – 1600 mA
- Operating 23% - 53% of rated value
- Fixture delivered lumens = up to 3,911 lumens
- Utilized to create NSP (12 degree)

CREE XML3 LED maximum rating 5,000 mA

- Spot (SP-19), Narrow Flood (NFL-25) and Flood (FL-40)
- Fixture operating milliamps = 1600
- Operating 32% of rated value
- Fixture delivered lumens = 5,000+ lumens

Last revised: 03/17/2025

Clarté Lighting

RR6-615-PAR38

Fixed Downlight

Ordering

Project Name:		Type:	
Catalog Number:		Date:	

(a) Driver	(b) Wattage	(c) LED	(d) Beam	(e) Snoot	(f) Reflector	(g) Diameter	(h) Housing	(i) Accessories	(j) Options	(k) Chromaticity
RR6-615-			-PAR38-							

Recessed Round 6" ID Trim

(a) Driver Options

E = ON/OFF (Electronic)
D = MLV 1% Dimming (2 wire)
ED = Electronic Reverse Phase Dimming 1% (2 wire)
0-10V1 = 0-10V 1% Dimming (3 wire)
RDM DMX = 0.01% - 100%, 4-channel for RGBW CAT5 in & out

(b) Wattage Options

45W (850 milliamps/2670 lumens) = 2 wire MLV
68W (1400 milliamps /4375 lumens) = ON/OFF, 0-10V 1%, DMX Dimming

(c) Lamp Type Options

XLED = Cree XPL2 LED @ All Wattages

(d) Beam Options

NSP = Narrow Spot NFL = Narrow Flood
SP = Spot FL = Flood

(e) Snoot Color Options

BLKS = Black Snoot
WHTS = White Snoot
PWTS = Pewter Snoot

(f) Reflector/Trim Lip Color Options

WHT/WHT = White Reflector/White Trim Lip
BLK/BLK = Black Reflector/Black Trim Lip
SA/WHT = Specular Reflector/White Trim Lip

(g) Outer Diameter Options

BR9-6 = Unitized Extended Lip 9 1/4"OD & 6"ID
BR10-6 = Separate Beauty Ring 10"OD & 6"ID
BR12-6 = Separate Beauty Ring 12"OD & 6"ID
BR15-6 = Separate Beauty Ring 15"OD & 6"ID

(h) Fixture Housing Options

Non-IC Rated:

NC = New Construction RET = Retrofit

(i) Optical and Accessory Options

LS = Lens Softener - +20% increase in beam width. Shields optical face visually. Softens edges of beam.



LSL = Linear Spread Lens - Horizontal or vertical beam elongation.



WFL = Wide Flood Lens - Wall washing increases the beam by 50% width with elimination of center beam.



LV = Louver - Small black hexcel louver eliminates all surface brightness. Creates stronger vertical cut off with -20% beam width.



CHL = Cross Hiar Louver



H = Halogen - 150K warmer. 2700k to 2550K



DH = Dimmed Halogen - 300K warmer. 2700k to 2400K

(j) Options

12V = DC
24V = DC
120V = 120VAC 60Hz (Standard)
230V = 230VAC 50Hz
277V = 277VAC 60Hz
347V = 347VAC 60Hz
EMG = 90min Emergency Back-Up Battery
TB = DMX 5-pin Plug-in Terminal Block
RMT = Remote transformer with remodel trim
80+ = CRI over 80
90+ = CRI over 90

(k) Color Temperature Options

White LED

22K* = 2200 Kelvin (candlelight color)
27K = 2700 Kelvin (incandescent color)
30K = 3000 Kelvin (halogen color)
35K = 3500 Kelvin (warm incandescent)
40K = 4000 Kelvin (cool incandescent)
50K = 5000 Kelvin (day white)
65K = 6500 Kelvin (12 noon sunlight)

Colored/Themed LED

UV365** = 365 NM UV black light
UV390** = 390 NM UV black light
Blue** = 465 - 485 NM wavelength
Green** = 520 - 535 NM wavelength
Amber** = 585 - 595NM wavelength
Red** = 620 - 630 NM wavelength
RGBW3K*** = Red, Green, Blue, White
RGBW4K*** = Red, Green, Blue, White

*1050 mA or less

**700 mA

***Must utilize DMX @ 700 mA

Clarté Lighting


RR6-615-PAR38

Fixed Downlight

Specifications

Project Name:		Type:	
Catalog Number:		Date:	

Retrofit Version with Separate Beauty Ring Option



Unitized Extended Lip with 9.25"OD:



Housing

- 100% aluminum construction

Electrical

- NON-IC fixture
- Optional - 12V AC remote class 2
- Optional - 12V or 24 DC remote class 2
- 100V, 120V, 230V, 277V or 347V

LED

- 3,000 maximum milliamp rated CREE LED
- Operates between 450 to 1200 milliamps
- L70 life = 100,000 hr.+

LED Driver

- D – 2 wire forward phase .01% LED driver fade to off glow to on
- ED – 2 wire reverse phase 1% LED driver
- DC – 12V or 24V
- 0-10V – 3 wire 1% LED driver
- Absolute Light – Remote mount class 2 48V din rail .001% LED system
- 16-bit RMD DMX – 65,536 dimming steps fade to off glow to on

Optics

- TIR discrete injection molded polycarbonate precision LED optic
- 45-degree vertical cut off

Trim

- .02" thin trim lip
- Hydro form reflector - no spin marks

Trim Finish

- Specular Aluminum Anodized
- Matt Aluminum Anodized
- White, Black or Pewter Powder Coat Paint
- 3300+ Custom Power Coat Paint Colors
- 7000+ Custom Wet Paint Colors

Level Plane and Trimless Installation

- Available in trimless ½" recessed, trimless and level plane

Installation

- Accommodates ceiling thickness up to 2.5"
- Universal adjustable 24" adjustable hangar bars


Certification

- UL Damp Listed – IP 52

Warranty

- 5 Year – ED, 0-10V, DMX and colored LED fixtures
- 7 Year – D and White LED fixtures

4 Trim Installation Options



Wattage & Lumen Output	
1400 Milliamps - 5000 Lumens	
68W	ON/OFF
	0-10V 1% Dimming
	DMX Dimming

3 Step CREE XPL2 LED	
Kelvin-CRI	Multiplier
27K-80+ CRI	1
27K-90+ CRI	0.80
30K-80+ CRI	1
30K-90+ CRI	0.85
35K-80+ CRI	105
35K-90+ CRI	0.9
40K-80+ CRI	109
50K-80+ CRI	109
65K-80+ CRI	105
80+ = 84 CRI	
90+ = 94 CRI	


RGBW V2 Light Output Luminous Flux Clarté Lighting offers 100% of fixtures in optional RGBW3K or RGBW4K			
	Line Voltage 600 mA RGBW3K	ABS Light 700 mA RGBW3K	700 mA White 3K
Red	1728	1920	
Green	3348	3720	
Blue	497	552	
White	2808	3120	
Total	8381	9312	3377
*RGBW Fixtures are designed to not operate with all 4 colors at 100% of light for more than 24hrs continuously and suggest operating 55% or less of all 4 colors ON to ensure optimum thermal life of the RGBW LED.			

Narrow Flood 21°		
2'	5,157 fc	0.7'
4'	1,289 fc	1.5'
6'	573 fc	2.2'
8'	322 fc	3.0'
10'	206 fc	3.7'
12'	143 fc	4.4'



67W PAR38 - 4,266 lm

Zonal Flux and Percentages		
Zone	Flux (lm)	%Luminaire
0-30	3369	79.0
0-40	3739	87.7
0-60	4197	98.4
0-90	4266	100.0
40-90	527	12.3
60-90	69	1.6
90-180	0	0.0
0-180	4266	100.0



Intensity Summary (cd)		
Gamma	All Planes	Flux (lm)
0	20628	
5	17468	1451
10	10916	
15	4848	1396
20	1966	
25	1066	522
30	764	
35	582	370
40	476	
45	381	295
50	291	
55	177	163
60	103	
65	73	65
70	14	
75	3	4
80	1	
85	0	1
90	0	

Clarté Lighting




RR6-615-PAR38

Fixed Downlight



TM-30 Color Metrics

Project Name:		Type:	
Catalog Number:		Date:	




Clarté Lighting 3000K 80+ CRI Color Metrics





CIE 13.3-1995 (CRI)
R _a 86
R _g 29






Clarté Lighting 3000K 90+ CRI Color Metrics





CIE 13.3-1995 (CRI)
R _a 95
R _g 74






Clarté Lighting 3000K 90+ CRI Halogen Lens (H) Color Metrics



CIE 13.3-1995 (CRI)
R _a 96
R _g 79



Clarté Lighting 3000K 90+ CRI Dimmed Halogen Lens (DH) Color Metrics



CIE 13.3-1995 (CRI)
R _a 95
R _g 64

