


SMR1-601-PAR8-ADJ-WL

IP66 Wet Listed Adjustable Mono Point

Project Name:		Type:	
Catalog Number:		Date:	

**Key Features**

- UL = IP66 Wet Listed
- ADA Compliant = 1.625" depth
- 3/4" ID & 1" OD LED Optic
- 3 Beam Spreads – Spot (17°), Narrow Flood (26°) or Flood (40°)
- Class 2 = 12V, 24V or 48V
- Accepts Up to 3 Optical Accessories

LED Source Details

CREE XHP50.2 LED maximum rating = 1500 mA

- Operating Range = 350 mA to 700 mA
- Operating 15% to 38% of Rated Value
- Fixture Wattage Range = 5W to 14W
- Fixture Delivered Lumens = 450 to 900 Lumens


Patent No.: US 10,208,928 B1
Other Patents Pending

Last revised: 01/05/2026

SMR1-601-PAR8-ADJ-WL

IP66 Wet Listed Adjustable Mono Point

Project Name:		Type:	
Catalog Number:		Date:	

**(a) Driver Options**

D	= 0.1% MLV 12V AC Dimming (2 wire)
E	= ON/OFF (Electronic)
ED	= 1% Electronic Reverse Phase Dimming (2 wire)
12V AC	= 0.1% PWM AC Remote Magnetic Dimming (2 wire)
24V DC	= 0.1% PWM DC Remote Magnetic Dimming (2 wire)
0-10V*	= Remote Mount 0-10V driver for single fixture (4 wire)
0-10V 2	= Remote Mount 0-10V driver for up to 2 fixtures (4 wire)
0-10V 3	= Remote Mount 0-10V driver for up to 3 fixtures (4 wire)
0-10V 4**	= Remote Mount 0-10V driver for up to 4 fixtures (4 wire)
DALI2	= 0.1% Digital Addressable Lighting Interface V2
DALI2-4***	= 0.1% Digital Addressable Lighting Interface V2 (4 fixture)
RDM DMX	= 0.001% 16 Bit, 4-Channel Dimming (2 wire with CAT5)
ABS	= 0.001% Absolute Light Dimming (use with RGBW)
ABSX	= 0.001% DMX Absolute Light Dimming (use with RGBW)

*Remote 0-10V LED driver operates single fixture up to 18' away 18ga and 50' away 12ga

**Remote 0-10V LED driver operates up to 4 fixtures up to 18' away 18ga and 50' away 12ga

***Operates up to 4 recessed LED light fixtures with remote LED driver

(b) Wattage Options

5W*	= ED, ON/OFF, 0-10V 1% (350 milliamps), 450 lumens
7W	= MLV <1% Dimming (350 milliamps), 450 lumens
10W	= Absolute Light
11W*	= ED, ON/OFF, 0-10V 1% (700 milliamps), 900 lumens
14W	= MLV <1% Dimming (700 milliamps), 900 lumens
15W*	= ED, ON/OFF, 0-10V 1%

*Only with no accessories

(c) LED Type Options

X4LED	= Cree XHP50.2 LED
-------	--------------------

(d) Beam Options

SP	= Spot 17°	NFL	= Narrow Flood 26°
FL	= Flood 40°	LM	= Luminosity Flood 50° Vertical Illumination with 5/8" glow extension

(e) Fixture Color Options

BLK*	= Black
WHT*	= White
PWT*	= Pewter
Select Custom Color (Review Website for Over 3,300 Color Options)	

*Zinc based powder coat paint for weatherization

(f) Installation Options

2CP	= 2" Canopy Plate	SPK	= Ground Spike
2.75CP	= 2.75" Canopy Plate	WM	= Wall Mount 90° Elbow
4.5CP	= 4.5" Canopy Plate	WC	= Wiring Compartment
CM	= Center Mount	CML	= Center Mount Lock

(g) Stem Options

S6	= Stem Size 6"	S18	= Stem Size 18"
S12	= Stem Size 12"	CS	= Custom Stem (up to 96" for flat canopy)

(h) Optical and Accessory Options

LS	= Lens Softener - +20% increase in beam width. Shields optical face visually. Softens edges of beam.	
LSL	= Linear Spread Lens - Horizontal or vertical beam elongation.	
WFL	= Wide Flood Lens - Wall washing increases the beam by 50% width with elimination of center beam.	
LV	= Louver - Small black hexcel louver eliminates all surface brightness. Creates stronger vertical cut off with -20% beam width.	
CHL	= Cross Hiar Louver	
H	= Halogen - 100K warmer. 2700k to 2500K	
DH	= Dimmed Halogen - 400K warmer. 2700k to 2300K	

(i) Options

RMT14	= 14Watt 12V AC MLV Step Down Transformer
RMT60	= 60Watt 12V AC MLV Step Down Transformer
RMT150	= 150Watt 12V AC MLV Step Down Transformer
RMT300	= 300Watt 12V AC MLV Step Down Transformer
120V	= 120VAC 60Hz (Standard)
230V	= 230VAC 50Hz
277V	= 277VAC 60Hz
80+	= CRI over 80
90+	= CRI over 90

(j) Color Temperature Options

White LED		Colored/Themed LED	
27K	= 2700 Kelvin (incandescent color)	RGBW3K*	= Red, Green, Blue, White
30K	= 3000 Kelvin (halogen color)	RGBW4K*	= Red, Green, Blue, White
35K	= 3500 Kelvin (warm incandescent)		
40K	= 4000 Kelvin (cool incandescent)		
50K	= 5000 Kelvin (day white)		

*Must utilize DMX fixture option

SMR1-601-PAR8-ADJ-WL


IP66 Wet Listed Adjustable Mono Point

Project Name:		Type:	
Catalog Number:		Date:	


WC (Wiring Compartment)

Remote 12V MLV Transformer

(2.75" plate with fixture mounting holes)



2.75" plate with fixture mounting holes

**Housing**

- 100% aluminum construction

Electrical

- Optional - 12V AC remote magnetic class 2 transformer
- 120V, 230V, or 277V

LED

- CREE XHP50
- 1500 milliamps maximum
- Operates between 350 to 700 milliamps
- 100,000+ L70 life

LED Driver

- D – 2 wire forward phase .01% LED driver fade to off glow to on
- ED – 2 wire reverse phase 1% LED driver - up to 4 fixtures
- 0-10V – 4 wire 1% LED driver
- 0-10V4 – 4 wire 1% LED driver, up to 4 fixtures
- Absolute Light – Remote mount class 2 48V din rail .001% LED system
- ABSX – DMX Absolute Light .001% RGBW dimming

Optics

- TIR discrete injection molded polycarbonate precision LED optic
- 45-degree vertical cut off

Installation

- EMT Connector – Push Lock EMT Connector Installation


Certification

- UL Wet Listed – IP66

Warranty


- 5 Year = 100,000 hr. L70 life

Ground Spike = SPK

**Stem**

Stem available in
6", 12", & 18"
*Custom sizes available
upon request.

New Construction and Retrofit



SMR1-601-PAR8-ADJ-WL

IP66 Wet Listed Adjustable Mono Point

Project Name:		Type:	
Catalog Number:		Date:	

Wattage & Lumen Output

300 Milliamps - 500 Lumens		700 Milliamps	
5W	ON/OFF 0-10V 1% Dimming ED	10W	Red - Up to 150 Lumens Green - Up to 150 Lumens Blue - Up to 150 Lumens White - Up to 300 Lumens
7W	MLV <1% Dimming		
525 Milliamps - 900 Lumens		700 Milliamps - 1150 Lumens	
11W	ON/OFF 0-10V 1% Dimming ED	15W	ON/OFF 0-10V 1% Dimming ED
14W	MLV <1% Dimming	14W	MLV <1% Dimming DMX

3 Step CREE XPL2 LED

Kelvin-CRI	Multiplier
27K-80+ CRI	1
27K-90+ CRI	0.80
30K-80+ CRI	1
30K-90+ CRI	0.85
35K-80+ CRI	105
35K-90+ CRI	0.9
40K-80+ CRI	109
50K-80+ CRI	109
65K-80+ CRI	105
80+ = 84 CRI	
90+ = 94 CRI	

RGBW V2 Light Output Luminous Flux
Clarté Lighting offers 100% of fixtures in optional RGBW3K or RGBW4K

	700 mA RGBW3K	700 mA White 3K
Red	160	
Green	310	
Blue	46	
White	260	
Total	776	907

*RGBW Fixtures are designed to not operate with all 4 colors at 100% of light for more than 24hrs continuously and suggest operating 55% or less of all 4 colors ON to ensure optimum thermal life of the RGBW LED.

Narrow Flood 26°

2'	559 fc	0.9'
4'	140 fc	1.9'
6'	62 fc	2.8'
8'	35 fc	3.7'
10'	22 fc	4.7'
12'	16 fc	5.6'

11W PAR8 - 525mA - 670 lm

Narrow Flood 26°

2'	699 fc	0.9'
4'	175 fc	1.9'
6'	78 fc	2.8'
8'	44 fc	3.7'
10'	28 fc	4.7'
12'	20 fc	5.6'

15W PAR8 - 700mA - 893 lm

Flood 40°

2'	402 fc	1.5'
4'	101 fc	2.9'
6'	45 fc	4.4'
8'	25 fc	5.9'
10'	16 fc	7.4'
12'	11 fc	8.8'

11W PAR8 - 525mA - 907 lm

Flood 40°

2'	503 fc	1.5'
4'	127 fc	2.9'
6'	57 fc	4.4'
8'	32 fc	5.9'
10'	20 fc	7.4'
12'	14 fc	8.8'


15W PAR8 - 700mA - 1209 lm

Zonal Flux and Percentages

Zone	%Luminaire
0-20	63
0-30	83.3
0-40	89.8
0-60	95.8
0-80	99.2
0-90	100
10-90	77.9
20-40	26.7
20-50	30.6
40-70	8
60-80	3.4
70-80	1.4
80-90	0.8

Zonal Flux and Percentages

Zone	%Luminaire
0-20	47.3
0-30	74.3
0-40	88.5
0-60	97.5
0-80	99.5
0-90	100
10-90	87.1
20-40	41.2
20-50	48.7
40-70	10.1
60-80	2
70-80	0.9
80-90	0.5

Axial Candela Display

Maximum Candela = 2237 - Located At Horizontal Angle = 0, Vertical Angle = 0
H - Horizontal Axial Candela
V - Vertical Axial Candela

Axial Candela Display

Maximum Candela = 1615 - Located At Horizontal Angle = 0, Vertical Angle = 0
H - Horizontal Axial Candela
V - Vertical Axial Candela

Clarté Lighting




SMR1-601-PAR8-ADJ-WL

IP66 Wet Listed Adjustable Mono Point



TM-30-18 Color Metrics

Project Name:		Type:	
Catalog Number:		Date:	




Clarté Lighting 3000K 80+ CRI Color Metrics





CIE 13.3-1995 (CRI)
R _a 86
R _g 29






Clarté Lighting 3000K 90+ CRI Color Metrics





CIE 13.3-1995 (CRI)
R _a 95
R _g 74






Clarté Lighting 3000K 90+ CRI Halogen Lens (H) Color Metrics



CIE 13.3-1995 (CRI)
R _a 96
R _g 79



Clarté Lighting 3000K 90+ CRI Dimmed Halogen Lens (DH) Color Metrics



CIE 13.3-1995 (CRI)
R _a 95
R _g 64

